



DpuScan

Janich & Klass
Computertechnik GmbH



DpuScan 7

Reference Manual

TWAIN Scanner

Copyrights

© 1997 to 2024 © Janich & Klass Computertechnik. All rights reserved.

Printed in Germany. The information contained in this documentation is the property of © Janich & Klass Computertechnik, Wuppertal. Neither receipt nor possession hereof confers or transfers any right to reproduce or disclose any part of the contents hereof, without the prior written consent of Janich & Klass, Wuppertal

Trademarks

The DPU logo is a registered trademark of © Janich & Klass Computertechnik. All other product names and logos are trademarks or registered trademarks of their representative companies.

Disclaimer

The instructions and descriptions in this manual were accurate at the time of this manual's printing. However, we reserve the right to alter the description and/or the product at anytime without prior notice. As per the actual state of software technique it is not possible to develop programs that will work trouble-free under all conditions and in any configuration. © Janich & Klass Computertechnik assume no liability for damages incurred directly or indirectly from errors, omissions, or discrepancies between this manual and the product.

Actuality

It may happen that a more recent version of this manual for DpuScan is available for download from the Internet. Therefore, it is recommended that you should compare the version by means of the date printed on this page with the version on the Internet. You should please use the most up-to-date version of the manual.

Table of Contents

1 DPUTWAIN Configuration	6
1.1 TWAIN	6
1.1.1 Twain More	8
Twain Barcode	11
1.2 TW-Specials	12

1 DPUTWAIN Configuration

The DPUTWAIN driver interfaces TWAIN scanner drivers to DPU applications.

To configure the driver interface and to setup TWAIN scanning parameters there are the following dialog pages and subsequent dialogs:

TWAIN	TWAIN Scanner Configuration
TWAIN more	Further settings, in particular for the communication process and special scanner settings
TWAIN Barcode	Settings for the hand over of the scanner's barcode search result.
TW-Specials	Special settings around TWAIN driver interface.

1.1 TWAIN

The TWAIN "User Interface", that is the scanner's setup dialog provided by the TWAIN driver, is available here.

Also, some operation parameters for the DPUTWAIN driver can be selected.

Depending on the capabilities of the scanner some of these controls may be not available.

TWAIN Setup The following values indicate how the scanner should be operated.

Show User Interface .. This button opens the TWAIN driver's setup dialog. Make all scanner related settings in this dialog.
For the other settings there consult the manual of the scanner manufacturer for help.

Note: The "User Interface" dialog must be closed before further DPU settings or testscans can be done.

Note: Some TWAIN scanner offer to save your settings when you **exit the setup dialog**. This is useful for other programs that don't have own storage options. So if you use the scanner with other software too, you should ensure that the settings are not overwritten. In this case you should just cancel the Save dialog, or leave it with "no".

Show User Interface while Scanning If checked, the "User Interface" will be open while scanning process.

In general, it makes more sense to hide the dialog, because the functions start / stop can also be performed by the program.

So it is recommended not to activate this feature. But it may happen that the driver of the scanner requires this procedure. If so, the parameters should be changed with care; the DPU scanning software assumes some parameters to be constant while scanning!

ON or OFF, Default: **OFF**

Show Indicators Shows - if exists - a status dialog of the scanner on the screen while scanning. This can be, for example, a progressbar for a flatbed scanner.

ON or **OFF**, Default: **OFF**

Advanced Settings

The following values defines how the communication shall be carried out between the program and the driver. These settings are determined automatically and should be changed only in a case of a failure.

check FEEDERLOADED before starting feeder

Should be set to ON normally. Set to OFF if:

Autoselect Feeder/Flatbed

- (1) paper detection does not work (machine does not start but reports 'no more paper');
- (2) the scanner supports feature 'automatic switching to flatbed if feeder is empty' and you want to use this.

Note: check FEEDERLOADED is not processed when 'Show User Interface while Scanning' is selected.

ON or **OFF**, Default: **ON**

Image Transfer Mode

Memory

In this mode the images can be transferred compressed. This may save time.

Native

This basic mode is defined for all TWAIN scanner and should work always.

Default: **Memory**

Bitonal Transfer Compression

G4

Transfers black/white images compressed by the CCITT method G4.

Uncompressed

Transfers black/white images uncompressed

Panel

Uses the parameters as set in the scanner driver or at the machine.

Default: **G4**

Gray/Color Transfer Compression

JPEG

Transfers gray images and color images compressed by the JPEG method

Uncompressed

Transfers gray images and color images uncompressed.

Panel

Uses the parameters as set in the scanner driver or at the machine.

Default: **JPEG**

Bitonal Photometric Uncomp.

Defines the interpretation of the image data for black/white images. This can be set for **G4** and **uncompressed** images separately.

G4

normal: Ones will be interpreted as black, zeros as white.

Reverse: Zeros will be interpreted as black, ones as white

If the scanner serves the TWAIN-Capability **TWEI_PIXELFLAVOR** , also this values may be used.

XImg Info: Interpretation as given in the XImg information

rev. XImg Info: Reversed interpretation as given in the XImg information

Default: **normal, normal**

Paper Side Info

Specifies how to determine whether the side is a front or back.

by DS:

Only the information from the DS (also know as DATASOURCE) is used..

by DS/Counter:

First it will be tried to get the information from the DS. Then, if this doesn't exists, the internal counter is used.

by DS/Counter

The internal counter is used.

Default: **DS/Counter**

more ...

Opens a further further dialog to determine the procedures after leaving the driver's setting.

.

1.1.1 Twain More

This setting is normally preset already correctly when loading the driver. Please change it only if you have detailed knowledge of the processes or if you are prompted to after consultation with us.

set CAP_AUTOFEED

If switched on, the scanner automatically pulls in the next page from the document feeder after a successful scan.

set CAP_AUTOSCAN

Sometimes a scanner is able to scan in auto mode (queuing mode), but does not confirm this capability at startup phase.

Enabling this checkbox will override this and mark the scanner as ready for auto scan.

get DAT:IMAGEINFO in.

Choose, when to operate DAT_IMAGEINFO / MSG_GET to read the general image description information. Standard is State 7 (that's when image data transfer is ready).

Some TWAIN driver handle over incorrect informations in State 7; image data interpretation fails then. Choose State 6 (that's just before image data transfer starts) in those cases.

**send
MSG_STOPFEEDER**

The Program can stop the scanning in queuing mode with the TWAIN command MSG_STOPFEEDER only.

This command should be available if the scanner has the capability CAP_AUTOSCAN (scanning in queuing mode).

Define here how this command should be sent:

normal

The command will just be sent.

never

The command will never be sent. This is useful for **older scanner** models not knowing this command and throwing an error instead.

always

There are scanners knowing the command but doesn't working in queuing mode. If such a device doesn't work correctly in **normal** mode use **always**.

**Alternatively send
PENDINGXFERS/RESET**

If activated, in case of a stop feeder request from application, and if MSG_STOPFEEDER does not work or is disabled (send never), MSG_RESET is send to the TWAIN scanner.

to stop feeder

This will stop most scanner models, but buffered prescanned images will be lost.

**Avoid
PENDINGXFERS/RESET**

Disables the attempt to stop the scanner with the Reset-Command when the scan application wants to break the scanning process.

Thus will keep the prescanned images.

To break the process the operator has to press the stop button at the device.

**Limit MemXFer Block
Size**

In case of errors during the image transfer from the scanner to the receiving application, the size of the transferred memory blocks can be specified.

For that the data source can be asked for the smallest, largest and preferred size of the buffer.

unlimited / Complete Image Size

Send the image in one block if possible.

DS:Preferred Value

Send the image in blocks of the preferred size as given by the driver (data source)

DS:MinBufferSize

Send the image in smallest blocks as possible and allowed by the by the driver (data source).

DS:MaxBufferSize

Send the image in largest blocks as possible and allowed by the by the driver (data source).

**While MemXfer
ignore
DS:MinBufferSize
ignore**

In case of a transfer errors you can try to override the values suggested by the driver (data source). You can try to ignore the minimum the maximum or both values for the block size.

**DS:MaxBuffersize
limit****Realloc MemXfer
Blocks
in steps of**

Here one can specify the size steps which shall be used to enlarge or reduce the memory allocated currently for the next (smaller or larger) image.

**store TWEI
Barcode Information
in Image Header**

Allows to hand over the barcode search result in the Image Header.

BC-Setup...

This button will open a configuration dialog for the barcode search options.

**always get
Extra&Imageinfo
(TWEI)**

Always fetches the TWEI values, even if no barcode was found.

Add ICC profile...

Allows loading of ICC profiles for the front and rear cameras. These are tables that assign precisely defined color values to the scanned color values.

The control elements below helps to locate and load the ICC profile files.

Delay Endxfer

Delays the check for the end of transfer.

**Throw No Paper after
unbuffered scan.**

Throws the error „No Paper“ after each scan in non-queuing mode. It's up to the scan application to handle this error, for example to display a message. Otherwise the scanner will wait for the next paper or a timeout.

**After scanning unload
and reload DS**

This option unloads and reloads the driver after scanning. This will release locked resources.

on MSG_CLOSEDOK

Choose what to process when TWAIN command MSG_CLOSEDREQ occurs (when User Interface closes):

D+C+O+P (default)

The TWAIN-driver will be **d**isabled, then **c**losed, then **o**pened again and then the **p**arameters will be read again.

This works with all scanners but takes a little time because the driver will be reloaded.

D+P

The TWAIN-driver will be **d**isabled then and then the **p**arameters will be read again. This is faster but not all TWAIN-Scanners support this method.

D+P+C

The TWAIN-driver will be **d**isabled then and then the **p**arameters will be read

**Load PresetFile
before ENABLE_DS**

Loads the settings from a Preset File, formerly exported by the driver in the user interface.

The following controls will help to locate the file and to specify the behavior if the file cannot be found at run time. "MessageBox will show a message, where throw ScanError 05556 will just inform the scan application.

1.1.1.1 Twain Barcode

If the scanner offers barcode recognition, detected barcodes will be returned by ImageHeader. To enable barcode search, please in the scanner's TWAIN settings enable the search.

To transfer barcode data by ImageHeader, enable this feature at in the TWAIN-More Dialog, option TWEl Barcode Info in ImageHeader

Set up positioning and format within ImageHeader by the following values:

Start	Usually value for the start is position 436 in the image header.
Length	Usually value for the length is 76 (the ImageHeader has got a maximum length of 512)
Text	<p>The usual text is %[BC-Text]</p> <p>%[BC-Text] – all decoded barcodetext in a row, separated by the specified separation character</p> <p>This can be followed by the following specifications:</p> <p>%[Type] – a two digit number representing the barcode type, which can be</p> <ul style="list-style-type: none">01 = EAN802 = EAN1302 = UPCA04 = 3OF9

05 = 2OF5INTERLEAVED
 06 = 2OF5MATRIX
 07 = 2OF5DATALOGIC
 08 = 2OF5INDUSTRIAL
 10 = CODABAR
 11 = CODABARWITHSTARTSTOP
 12 = 3OF9FULLASCII
 13 = CODE128
 14 = 2OF5IATA
 15 = UPCE
 19 = CODE93
 20 = PDF417
 21 = UCC128
 22 = QRCODE
 23 = DATAMATRIX
 24 = AZTEC
 25 = 2OF5NONINTERLEAVED (TWAIN; what ever that is)
 26 = POSTNET
 27 = MAXICODE
 99 = unknown type

Others:

%[PosX] – horizontal position of barcode within image, 5 digits, leading zeroes, pixels

%[PosY] – vertical position of barcode within image, 5 digits, leading zeroes, pixels

%[Confidence] – there might be errors during barcode decoding, gives the confidence of result

%[Rotation] – rotation or orientation of the barcode within image 0, 1 (90°), 2 (180°), 3 (270°), 4 else

Note: Most likely, the scanner only gives %[BC-Text] and %[Type], so it is useless to specify the others.

Please check the scanner's manual for details.

Separation

Usual is the comma ",", but should be set to some *rare* character which will certainly not come with the decoded barcode.

Especially with the 2D barcodes a normal punctuation, such as comma, full stop, exclamation mark, etc can be part of the information stored with the barcode.

They will not work as a character to separate several detected barcodes from one page.

- A useful character to separate multiple result barcodes will be: `ÿ` (Alt-0255)

- Another character to separate %[BC-Text] from %[Type] is: `p` (Alt-0254)

Not-Found Text

This is a replacement text in case there are no barcodes found.

1.2 TW-Specials

On this page, preferences for controlling the driver can be set, e.g. the program's brightness and contrast sliders can be linked directly to the corresponding functions of the driver. Of course, this only works if the scanning program supports this on its side.

Please change it only if you have detailed knowledge of the processes or if you are prompted to after consultation with us.

Restart the application to apply the changes!



Values other than default ones should be selected by experts only!
Changes will take effect only when the application starts next time!
The configuration is global for all TWAIN scanners used by this interface

Special Extra Settings These settings determine how the scanner's TWAIN dialog is integrated

Subclass Dialog

Subclass Dialog

If checked, the TWAIN driver's dialog gets sub-classed to the current application. Should be changed by experts only!

Restart the application to apply changes!

send Timer MSGs

These settings determine whether permanently displayed driver windows should receive synchronization messages.

Allow Control by Application

With these options, important settings can be made directly from the program. If these options are switched off, it is only possible to make these settings directly in the driver dialog.

These options should only be activated if the corresponding setting option in the program is actually used.

Color Mode

Color Mode

If checked, the application selects the color mode (black&white, gray, color). Selection in TWAIN's User Interface has no effect then.

Restart the application to apply changes!

Resolution

Resolution

If checked, the application selects scanning resolution. Selection in TWAIN's User Interface has no effect then.

Restart the application to apply changes!

Brightness

Brightness

If checked, the application can change scanner's brightness.

Restart the application to apply changes!

... reversed Values

Brightness - reversed Values

Check to reverse application's brightness slider direction.

Threshold

Threshold

If checked, the application sets the scanner's threshold value. Threshold value set in TWAIN's User Interface has no effect then.

Restart the application to apply changes!

... reversed Values

Threshol - reversed Values

Check to reverse application's threshold slider direction.

Contrast

Contrast

If checked, the application can change scanner's contrast.

Restart the application to apply changes!

... reversed Values Contrast - reversed Values

Check to reverse application's contrast slider direction.

Paper Source Paper Source

If checked, the application can change scanner's paper source (flatbed, autofeeder).

Restart the application to apply changes!

Paper Size Paper Size

If checked, the application selects the scan area. Selection in TWAIN's User Interface has no effect then.

Restart the application to apply changes!

Endorser Endorser

If checked, the application can change scanner's endorser/imprinter text and counter.

Restart the application to apply changes!

Index

- A -

After scanning 8
Allow control by Application 12
Autoselect Feeder/Flatbed 6

- B -

Barcode 11
Barcode Information 8
Barcode Length 11
Barcode Not-Found Text 11
Barcode Separation 11
Barcode Start 11
Barcode Text 11
Barcodes 6
Behave 6
Bitonal Photometric 6
Bitonal Transfer Compression 6
Block Size 8
Brightness 12
BufferSize 8

- C -

CAP_AUTOFEED 8
CAP_AUTOSCAN 8
Code128 11
Code2/5 11
Code39 11
Color Mode 12
Contrast 12

- D -

Datamatrix 11
Dialogue pages 6
DPU interface 6
DPUTWAIN 6

- E -

Endorser 12
English 6
Explanations 6
Extra Imageinfo (TWEI) 8

- G -

Gray/Color Transfer Compression 6

- I -

ICC profile 8
Image Transfer Mode 6
Interface 6

- L -

Load PresetFile 8
Load ProfiletFile 8

- M -

MemXFer 8
More 6
MSG_CLOSEDOK 8
MSG_STOPFEEDER 8

- O -

operation parameters 6

- P -

Paper Side Info 6
Paper Size 12
Paper Source 12
PENDINGXFERS/RESET 8
Program library 6

- Q -

QR 11

- R -

Resolution 12
Reversed Values 12

- S -

Scanning applications 6
Show Indicators 6

Show User Interface while Scanning 6
stop feeder 8
Subclass 12

- T -

Transmission parameters 6
TWAIN 6
TWAIN configuration 6
TWAIN Interface Configuration 12
TWAIN Scanner Configuration 6

- U -

unbuffered scan 8
User Interface 6

Reference Manual TWAIN Scanner

© Janich & Klass Computertechnik

Wuppertal, Germany, 2024